

CHARTS

25

STANDARD UNITS - 1" (25mm) SET BACK

SAND/GRAVEL: ϕ =34°, γ =120 pcf (19kN/m³)






The information contained herein has been compiled by Keystone® Retaining Wall Systems, Inc. and to the best of our knowledge, accurately represents the Keystone product use in the applications which are illustrated. Final determination of the suitability for the use contemplated and its manner of use are the sole responsibility of the user. Structural design and analysis shall be performed by a qualified engineer.

www.keystonewalls.com Keystone Construction Manual

26


STANDARD UNITS - 1" (25mm) SET BACK

SILT/LEAN CLAY: ϕ =26°, γ =120 pcf (19kN/m³)



STANDARD UNITS - NEAR VERTICAL

SAND/GRAVEL: ϕ =34°, γ =120 pcf (19kN/m³)




The information contained herein has been compiled by Keystone® Retaining Wall Systems, Inc. and to the best of our knowledge, accurately represents the Keystone product use in the applications which are illustrated. Final determination of the suitability for the use contemplated and its manner of use are the sole responsibility of the user. Structural design and analysis shall be performed by a qualified engineer


Keystone Construction Manual www.keystonewalls.com

27

STANDARD UNITS - NEAR VERTICAL

SILTY SAND: ϕ =30°, γ =120 pcf (19kN/m³)





The information contained herein has been compiled by Keystone® Retaining Wall Systems, Inc. and to the best of our knowledge, accurately represents the Keystone product use in the applications which are illustrated. Final determination of the suitability for the use contemplated and its manner of use are the sole responsibility of the user. Structural design and analysis shall be performed by a qualified engineer.

www.keystonewalls.com Keystone Construction Manual